



MASTER PLUS

# Round balers Master

*High yield, great performance, high profitability, all with simplicity*

This model was created to press particularly difficult products, making any type of work possible. There are 3 versions:

SP MASTER 1200 (bale dimensions 120x120)

SP MASTER 1500 (bale dimensions 120x150)

SP MASTER 1650 (bale dimensions 120x165)

All of these are equipped as standard with a pressure chain with thicker crossbars which guarantees better wrapping of the product. The crossbars that are fixed respect to the chain create an integral forming belt.



The pick-up of the latest design makes possible to adjust the cams externally. The side screws of large diameter convey the picked product towards the centre. The 2200 mm width guarantees perfect harvesting, whilst the rotary feeder avoids entrapment and guarantees feeding of any product.




The net binder with direct introduction in the chamber (net is introduced by the rollers) assures tension right from the start of the binding and thanks to the controlled braking system it improves the binding quality of the external borders.



Electronic unit device:

- Partial and total counter of the bales
- Acoustic signal of bale ending
- Manual or automatic starting of net binding



Introduction of the product into the chamber is completed by the alternative feeder which guarantees constant feeding in order to obtain improved baling.

- The roller-chains system does not require the disengagement of the PTO at the moment of the opening of the chamber.
- The 2 lower rollers offset from each other make it even easier unloading the bales.

Tractor hydraulic equipment required for operation of the round baler:

- 1 single-acting for lifting/lowering the pick-up;
- 1 single-acting for opening/closing the tailgate.

The pressure in the chamber is controlled mechanically, by a system of levers placed on both sides of the machine.



#### MASTER PLUS - TRONIC

	1200	1500	1650
Length (mm)	3750	3850	4100
Width (mm)	2450	2450	2450
Height (mm)	2150	2340	2550
Weight (Kg)	2760	2910	2980
Min. power PTO KW/CV request	52 (70)	60 (80)	68 (90)
PTO (rpm)	540	540	540
Bale diameter (mm) Ø	1200	1500	1650
Bale width (mm)	1200	1200	1200
No. of rollers	5	6	6
Pickup width (mm)	2200	2200	2200
No. of pick-up teeth for row 160/190	28	28	28
Distance between teeth (mm)	70	70	70
Nr. 2 pick-up's tires	✓	✓	✓
Pick-up lifting	Hydraulic single - acting		
Net binder	Standard		
Tires	15.0/55-17	15.0/55-17	15.0/55-17
Optional tires	19.0/45-17	19.0/45-17	19.0/45-17

